



# AMX 775 C Colored Stucco

Product # AMX 775C



## 1. PRODUCT NAME:

Amerimix AMX 775C Colored Stucco

## 2. PRODUCT DESCRIPTION:

Amerimix Colored Stucco – AMX 775C is a colored, decorative, water resistant, Portland/lime-based stucco. It is factory blended to provide a uniform color finish. The pigments are finely milled and specially mixed to ensure proper dispersion throughout the batch. Conforms to ASTM C926.

### Features and Benefits:

- Factory blended under controlled conditions to meet strict quality control standards for color consistency and engineered performance tolerances
- Water resistant
- Outstanding workability for smooth spreading and quality finish
- Extended mortar board life, less re-tempering required
- Increased yield compared to typical field mix mortars

### Uses:

Use as a decorative finish over

- Cement Plaster
- Masonry Block
- Precast and cast in place concrete
- One, two, or three coat stucco system

### LEED Eligibility:

Regional Materials (MR-c5)

Recycled Material (MR-c4)

*NOTE: Amerimix products generally qualify for LEED Materials and Resources. Contact Technical Services for additional information regarding LEED qualifications for your specific product application and project location.*

### Packaging:

Available in 70 lb. (31.2 kg) bags

## Approximate Coverage:

Bag Size / Water	Yield – For Laying Brick, Block or Cultured Stone
70 lb. (31.2 kg) 1.75 – 2 gal (6.6 – 7.8L)	Yield: 50 – 60 ft <sup>2</sup> (4.6 – 5.6 m <sup>2</sup> ) at 1/8" (3 mm) thick 25 – 30 ft <sup>2</sup> (2.3 – 2.8 m <sup>2</sup> ) at 1/4" (6 mm) thick.

*NOTE: Yield and water are approximate. The yield above does not allow for waste and spillage. More water may be required to achieve desired consistency. Avoid overwatering*

## Safety:

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS sheets are available on our website [Amerimix.com](http://Amerimix.com) or you can contact CHEMTREC (24 hours availability) 800-424-9300 or contact Amerimix Technical Services at 800-334-0784.

## 3. TECHNICAL DATA:

### Testing Notes:

- Mortar is designed to meet the requirements of ASTM C270 Standard Specification for Mortar for unit Masonry. This is a laboratory test procedure.
- Mortar should be tested in the field by following ASTM C780, Standard Test Method for Preconstruction & Construction Evaluation of Mortar for Plain & Reinforced Unit Masonry.
- Due to the procedure differences between ASTM C270 & ASTM C780, the compressive strength values resulting from field sampled mortars are not required nor expected to meet the minimum compressive strengths of the property specification requirements of ASTM C270 as tested under controlled laboratory conditions nor do they represent the compressive strength of the mortar in the wall.

### Applicable Standards:

#### Refer to:

ACI 530.1 Specification for Masonry Structures

- Recommended Practices and Guide Specifications for Cold Weather Masonry Construction
- Recommended Practices and Guide Specifications for Hot Weather Masonry Construction

#### ASTM International (ASTM)

- ASTM C91 Standard Specification for Masonry Cement
- ASTM C150 Standard Specification for Portland Cement
- ASTM C207 Standard Specification for Hydrated Lime for Masonry Purposes
- ASTM C595 Standard Specification for Blended Hydraulic Cements

- ASTM C926 Standard Specification for Application of Portland Cement Based Plaster
- ASTM C979 Standard Specification for Pigments for Integrally Colored Concrete
- ASMT C1714 Standard Specification for Preblended Dry Mortar Mix for Unit Masonry

#### National Concrete Masonry Association (NCMA)

- NCMA TEK Bulletin #8-2A Removal of Stains from Concrete Masonry
- NCMA TEK Bulletin #8-3A Control and Removal of Efflorescence

## 4. PRE-CONSTRUCTION GUIDELINES

### Job Mock-Ups:

Amerimix requires that when Amerimix Colored Stucco – AMX 775C FBC is used in any application or as part of any system that includes other manufacturer's product, the contractor and/or design professional shall test all the system components collectively for compatibility, performance, and long-term intended use in accordance with pertinent and accepted industry standards prior to any construction. Written documentation of the test performed shall be satisfactory to the design professional and contractor. Test results must include the means and methods of application, products used, project-specific conditions being addressed, and standardized tests performed for each proposed system or variation. Approved mockups or sample panels should be retained until completion of the project.

## 5. INSTALLATION

### Preparation:

1. For best results all materials should be stored between 40°F (4°C) and 80°F (27°C) 24 hours prior to application.
2. Remove all loose particles, dirt, dust, or any foreign materials that would inhibit proper bonding to substrate.
3. New or existing surfaces that lack the proper surface profile for adhesion may require mechanical profiling, the application of a dash bond coat or the application of a bonding agent. The Sakrete Bonder & Fortifier can be used as a brush on primer.
4. Certain conditions may require the substrate to be SSD (saturated surface dry) conditioned such as dry windy climates, porous substrates, or high temperatures.

*NOTE: it is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.*

### Color Accuracy, Surface Uniformity, Samples, and Efflorescence:

1. AMX 775C is an engineered mix designed to provide accurate proportioning and a uniform formulation from bag to bag. However, color accuracy and colored uniformity are influenced by the moisture content of the substrate, the porosity of the surface, and the ambient environment.
2. Always provide a jobsite applied sample before ordering the premixed color for a project.
3. Water with high mineral salt content can cause efflorescence. Efflorescence occurs naturally with cement-based products and is beyond the control of Amerimix.

### Mixing:

1. Use of a mechanical mixer will help ensure a more uniform mix.
2. Use approximately 1.75 – 2.0-gal (6.6 – 7.8 L) of clean potable water per 70 lb. (31.2 kg) bag. Mix only quantities that be applied within one hour. What applying over porous substrates or during hot dry weather, mix ½ gal (1.9L) of Sakrete Bonder & Fortifier and 1.25-gal (4.7 L) of water with one 70 lb. (31.2 kg) bag.
3. Pour approximately ¾ of the required water amount into the mixer.
4. With the mixer running, add bags of dry colored stucco and mix thoroughly.
5. Add remaining water in small amounts as necessary to achieve optimum consistency and workability. Mix for a minimum of 5 minutes.
6. Let mix stand for 2 minutes to enable the absorption of water and re-mix.
7. Stucco should always be mixed to a workable consistency. Keep mixing consistent from batch to batch. CAUTION: Variations in water amounts will cause color variation in final color. A mix that is too dry and crumbly will not provide the proper bond. AVOID A SOUPY MIX. Stucco that is too wet will be weak and will not provide adequate bond to the substrate and can result in reduced strength, efflorescence, inconsistent color, cracking, dusting, or scaling.
8. Agitate material as necessary within its working time to maintain workability. Do not add any additional water.

### Application:

1. The optimal temperature range for mortar application is between 40°F and 90°F (4°C and 32°C). Application outside of this range is possible when appropriate precautions for cold or hot weather construction are implemented in compliance with ACI, PCA, ASTM or Masonry Institute standards.
2. Apply a minimum thickness of 1/8" (0.32 cm) and in accordance with ASTM C926 Standard Specification for Application of Portland Cement Based Plaster, local building code and applicable ASTM Standards.
3. Spray Application: Spray an even, consistent coat, moving the nozzle with a steady and even motion, maintaining the same distance and angle from the wall.
4. Smooth and float finishes are more likely to cure with a mottled effect. Do not over-float stucco surface.
3. Agitate material as necessary within its working time to maintain workability.
4. Do not add materials other than clean potable water.
5. Do not overwater. Avoid adding excessive amounts of water that promote segregation or bleeding of the stucco, loss of strength, durability and inconsistent color.
6. Color variations may result from differences in thickness, textures, weather, differing substrates, and application methods. Always prepare a test panel reflecting jobsite conditions.
7. Protect uncoated aluminum from direct contact with Portland cement-based materials.
8. Shelf life not to exceed one year from date of manufacture.

### Painting/Coating:

1. AMX 775C may be painted with acrylic or elastomeric coatings and recoated with a variety of polymer based textured coatings.
2. This is a cement/lime mix when applied the surface will reflect high pH values.

3. While pH levels of AMX 775 C may drop after the initial application, a number of environmental factors may cause the pH on the surface to go back up.
4. Use paints and coatings designed specifically for high pH surfaces. Refer to the paint/coating company's directions regarding primers, number of coats, and dried mil thicknesses for application of their pH tolerant coating systems.

*RE-TEMPERING NOTE: Agitate material as necessary within its working time to maintain workability. Do not add any additional water*

### **Curing:**

Loss of surface water may occur quickly due to higher ambient air temperatures and windy conditions. Fog spray as needed. Protect from rain and freezing for 24 hours.

### **Cleaning:**

- Use water to clean all tools immediately after use.
- Dried material must be mechanically removed.
- Only clean potable water should be used in the cleaning process.

### **Safety:**

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. **WARNING:** Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300. **KEEP OUT OF REACH OF CHILDREN.**

## **6. AVAILABILITY**

Amerimix products are available throughout the US and Canada. For more information, contact Amerimix at:  
Toll-Free: 866-725-7383  
Website: Amerimix.com

## **7. TECHNICAL SUPPORT**

For technical assistance please contact us at:  
Toll-Free: 866-725-7383

## **8. WARRANTY**

### **What Does This Warranty Cover?**

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. **ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY.** Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. **CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.**

### **How Long Does Coverage Last?**

This warranty lasts for a period of one (1) year from the date of purchase. **ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS LIMITED TO THE DURATION OF THIS**

**EXPRESS WARRANTY.** Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.

### **What Will Amerimix Do to Address Problems?**

Amerimix will replace the defective product or refund the purchase price, at its option.

### **What Does This Warranty Not Cover?**

Amerimix will not be liable for damage or loss resulting from a failure to store, use, install or maintain the product in strict accordance with Amerimix's specifications and instructions. In no event will Amerimix be liable for damages in excess of the purchase price for the product. **CONSEQUENTIAL, SPECIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

### **How Do I Get Warranty Service?**

Within thirty (30) days after discovering a defect in the product, contact Amerimix in writing at the following address:  
Amerimix Technical Support Group  
625 Griffith Road - Suite 100  
Charlotte, NC 28217  
Include with your letter a brief description of the problem and any sales receipt, invoice or other proof of the date of purchase. To obtain Amerimix's technical or sales literature, please call (888) 313-0755 or visit our website at Amerimix.com

### **How Does State Law Relate to This Warranty?**

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

### **DANGER:**

This product contains Crystalline Silica and Portland Cement which are known to cause cancer, eye damage, lung disease, respiratory damage, silicosis, skin burns, and other serious medical conditions. Harmful if swallowed and corrosive.

### **CAUTION:**

Do not handle or use this product until you review and understand the instructions, including the safety precautions. The applicable safety precautions include wearing protective clothing, protective eyewear, protective footwear, protective gloves, and respiratory protection when handling or working around this product. Protective clothing should include face protection, impervious gloves, long pants, and a long-sleeved shirt. Eye and respiratory protection must comply with the guidelines of the Occupational Health and Safety Administration (OSHA). Do not breathe or otherwise ingest the dust from this product. Wash hands and clothing after handling or working around this product. This product should only be used outdoors or in a well-ventilated area and the user should avoid creating dust. Dispose of unused concrete products in accordance with applicable law. Review the Safety Data Sheet, which is available online at [www.sakrete.com](http://www.sakrete.com), prior to handling or using this product.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

Seek medical attention if you experience skin burns or irritation. If you ingest this product, rinse your mouth with water and seek medical attention if you feel ill. In the event of eye irritation, remove any contact lenses and carefully rinse eyes with water for several minutes. If eye irritation persists, seek medical attention. If inhaled, relocate to an area with fresh air and seek medical attention if you feel ill.

**WARNING:**

This product can expose you to chemicals including Crystalline Silica, which is known to the State of California to cause cancer, and Lithium Carbonate, which is known in the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**ENVIRONMENTAL ADVISORY:**

Uncured or crushed cured cement is an environmental hazard which may adversely affect fish and wildlife. Dispose of construction debris containing cement, including empty bags, at a permitted municipal disposal firm. Do not use crushed concrete as a fill near an aquatic habitat.

Amerimix  
400 Perimeter Center Terrace, Suite 1000  
Atlanta, GA 30346  
Ph: 866-725-7383  
[Amerimix.com](http://Amerimix.com)