

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 01/15/2016 Revision Date: 01/31/2018 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking **Product identifier** 1.1. Product form : Mixture Product name : Amerimix Fiber Base Coat Concentrate Stucco (AMX 755) 65401036 - 3000 lb Product code 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture : Various. 1.3. Details of the supplier of the safety data sheet Oldcastle Architectural Inc. Three Glenlake Parkway, Floor 12 30328 Atlanta, GA - USA T 800-334-0784 Tech Service: Monday - Friday; 8:00am - 5:00pm EST **Emergency telephone number** 1.4.

Emergency number

CHEMTREC 1-800-424-9300 [USA] / +1 703-527-3887 [CAN]

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity 4 (Oral) Skin Irritation 2 Serious Eye Damage 1 Skin Sensitization 1 Carcinogenicity 1A Specific Target Organ Toxicity After Single Exposure 3 Specific Target Organ Toxicity After Repeated Exposure 1

2.2. Label elements

GHS-US labelling

Signal word (GHS-US)

Hazard statements (GHS-US)

Precautionary statements (GHS-US)

Hazard pictograms (GHS-US)



- : Danger
- : Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.
- Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Rinse mouth. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Store in a well ventilated place. Keep container tightly closed. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4.	Unknown acute toxicity (GHS-US)
23 % of	the mixture consists of ingredient(s) of unknown acute toxicity.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Cement, portland, chemicals	(CAS No) 65997-15-1	20 - 50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Ashes, residues	(CAS No) 68131-74-8	30 - 50	Not classified
Iron oxide (Fe2O3)	(CAS No) 1309-37-1	5 - 10	Not classified
Quartz	(CAS No) 14808-60-7	5 - 10	Acute Tox. 4 (Oral), H302 Carc. 1A, H350 STOT RE 1, H372
Calcium magnesium hydroxide (CaMg(OH)4)	(CAS No) 39445-23-3	3 - 7	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Calcium magnesium hydroxide oxide (CaMg(OH)2O)	(CAS No) 58398-71-3	3 - 7	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Magnesium oxide (MgO)	(CAS No) 1309-48-4	3 - 7	Not classified
Calcium hydroxide	(CAS No) 1305-62-0	1 - 5	Skin Corr. 1B, H314
Magnesium hydroxide	(CAS No) 1309-42-8	1 - 5	Not classified
Calcium sulfate	(CAS No) 7778-18-9	1 - 5	Not classified
Gypsum (Ca(SO4).2H2O)	(CAS No) 13397-24-5	1 - 5	Not classified
Limestone	(CAS No) 1317-65-3	1 - 5	Not classified
Calcium oxide	(CAS No) 1305-78-8	1 - 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

* Exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures after inhalation :	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.	
First-aid measures after skin contact :	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.	
First-aid measures after eye contact :	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.	
First-aid measures after ingestion :	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/ physician.	
4.2. Most important symptoms and effects,	both acute and delayed	
Symptoms/injuries after inhalation :	May cause respiratory tract irritation.	
Symptoms/injuries after skin contact :	Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.	
Symptoms/injuries after eye contact :	Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.	
Symptoms/injuries after ingestion :	Harmful if swallowed. May cause stomach distress, nausea or vomiting.	
4.3. Indication of any immediate medical at	tention and special treatment needed	
Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).		

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Treat for surrounding material.	
Unsuitable extinguishing media	: Not available.	
5.2. Special hazards arising from the sub	stance or mixture	
Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.	
01/15/2016	EN (English)	2/7

Safety Data Sheet

5.3. Advice for fir	efighters		
irefighting instructions		: Keep upwind of fire. Wear full fire fin protection (SCBA).	ghting turn-out gear (full Bunker gear) and respiratory
	lental release measu		
		pment and emergency procedures	
General measures		unnecessary and unprotected perso	ded in Section 8. Isolate the hazard area and deny entry to onnel.
	material for containmen		
or containment		waterways. Use appropriate Persor	
Methods for cleaning up	1	: Vacuum or sweep material and place	ce in a disposal container. Provide ventilation.
6.3. Reference to	other sections		
See section 8 for furthe	· information on protective	clothing and equipment and section 1	3 for advice on waste disposal.
SECTION 7: Hand			
	for safe handling		
Precautions for safe har	ıdling	housekeeping is important to preve cleaning clothing, equipment, etc, is	woid generating and breathing dust. Do not swallow. Good nt accumulation of dust. The use of compressed air for s not recommended. Use only outdoors or in a well-ventilated ith care. When using do not eat, drink or smoke.
Hygiene measures		: Launder contaminated clothing before	ore reuse. Wash hands before eating, drinking, or smoking.
7.2. Conditions for	or safe storage, including	any incompatibilities	
Storage conditions		tightly closed when not in use. Avoi	Store in dust-tight, dry, labelled containers. Keep container id any dust buildup by frequent cleaning and suitable o not store in an area equipped with emergency water in a well-ventilated place.
ECTION 8: Expo	sure controls/perso meters	nal protection	
Cement, portland, ch	emicals (65997-15-1)		
USA ACGIH	ACGIH TWA (mg	g/m³)	1 mg/m ³
USA OSHA	OSHA PEL (TW)	A) (mg/m³)	15 mg/m ³ (total); 5 mg/m ³ (resp)
Iron oxide (Fe2O3) (1	309-37-1)		
USA ACGIH			
USA ACGITI	ACGIH TWA (mg	g/m³)	5 mg/m ³
USA OSHA		5 ,	5 mg/m ³ 10 mg/m3
USA OSHA	ACGIH TWA (mg	5 ,	
	ACGIH TWA (mg	A) (mg/m ³)	
USA OSHA Quartz (14808-60-7)	ACGIH TWA (mg OSHA PEL (TW	g/m ³)	10 mg/m3
USA OSHA Quartz (14808-60-7) USA ACGIH	ACGIH TWA (mg OSHA PEL (TWA ACGIH TWA (mg OSHA PEL (TWA	g/m ³)	0.025 mg/m ³ (30)/(%SiO2 + 2) mg/m ³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp)
USA OSHA Quartz (14808-60-7) USA ACGIH USA OSHA	ACGIH TWA (mg OSHA PEL (TWA ACGIH TWA (mg OSHA PEL (TWA	A) (mg/m ³) g/m ³) A) (mg/m ³)	0.025 mg/m ³ (30)/(%SiO2 + 2) mg/m ³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp)
USA OSHA Quartz (14808-60-7) USA ACGIH USA OSHA Magnesium oxide (M	ACGIH TWA (mg OSHA PEL (TWA ACGIH TWA (mg OSHA PEL (TWA g0) (1309-48-4)	A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³)	0.025 mg/m³ (30)/(%SiO2 + 2) mg/m³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp) (10)/(%SiO2 + 2) mg/m³ TWA, (resp)
USA OSHA Quartz (14808-60-7) USA ACGIH USA OSHA Magnesium oxide (M USA ACGIH USA OSHA	ACGIH TWA (mg OSHA PEL (TW) ACGIH TWA (mg OSHA PEL (TW) gO) (1309-48-4) ACGIH TWA (mg OSHA PEL (TW)	A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³)	0.025 mg/m³ (30)/(%SiO2 + 2) mg/m³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp) (10)/(%SiO2 + 2) mg/m³ TWA, (resp)
USA OSHA Quartz (14808-60-7) USA ACGIH USA OSHA Magnesium oxide (M USA ACGIH	ACGIH TWA (mg OSHA PEL (TW) ACGIH TWA (mg OSHA PEL (TW) gO) (1309-48-4) ACGIH TWA (mg OSHA PEL (TW)	A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³) A) (mg/m ³)	0.025 mg/m³ (30)/(%SiO2 + 2) mg/m³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp) (10)/(%SiO2 + 2) mg/m³ TWA, (resp)
USA OSHA Quartz (14808-60-7) USA ACGIH USA OSHA Magnesium oxide (M USA ACGIH USA OSHA Calcium hydroxide (*	ACGIH TWA (mg OSHA PEL (TW) ACGIH TWA (mg OSHA PEL (TW) g0) (1309-48-4) ACGIH TWA (mg OSHA PEL (TW)	A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³) A) (mg/m ³)	10 mg/m3 0.025 mg/m³ (30)/(%SiO2 + 2) mg/m³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp) (10)/(%SiO2 + 2) mg/m³ TWA, (resp) 10 mg/m³ 15 mg/m³
USA OSHA Quartz (14808-60-7) USA ACGIH USA OSHA Magnesium oxide (M USA ACGIH USA OSHA Calcium hydroxide (* USA ACGIH	ACGIH TWA (mg OSHA PEL (TWA OSHA PEL (TWA OSHA PEL (TWA OSHA PEL (TWA ACGIH TWA (mg OSHA PEL (TWA I305-62-0) ACGIH TWA (mg OSHA PEL (TWA	A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³) A) (mg/m ³)	10 mg/m3 0.025 mg/m³ (30)/(%SiO2 + 2) mg/m³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp) (10)/(%SiO2 + 2) mg/m³ TWA, (resp) 10 mg/m³ 15 mg/m³ 5 mg/m³
USA OSHA Quartz (14808-60-7) USA ACGIH USA OSHA Magnesium oxide (M USA ACGIH USA OSHA Calcium hydroxide (* USA ACGIH USA OSHA	ACGIH TWA (mg OSHA PEL (TWA OSHA PEL (TWA OSHA PEL (TWA OSHA PEL (TWA ACGIH TWA (mg OSHA PEL (TWA I305-62-0) ACGIH TWA (mg OSHA PEL (TWA	A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³) A) (mg/m ³) g/m ³)	10 mg/m3 0.025 mg/m³ (30)/(%SiO2 + 2) mg/m³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp) (10)/(%SiO2 + 2) mg/m³ TWA, (resp) 10 mg/m³ 15 mg/m³ 5 mg/m³

USA OSHA

OSHA PEL (TWA) (mg/m³)

15 mg/m3

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Calcium sulfate (777	(8-18-9)	
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m³ (total); 5 mg/m³ (resp)
Gypsum (Ca(SO4).2	H2O) (13397-24-5)	
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total); 5 mg/m ³ (resp)
Limestone (1317-65-	3)	
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m³ (total); 5 mg/m³ (resp)
Calcium oxide (1305	-78-8)	
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear suitable waterproof gloves.
Eye protection	: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
Skin and body protection	: Wear suitable waterproof protective clothing.
Respiratory protection	: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
Other information	: Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	d chemical properties	
Physical state	: Solid.	
Appearance	: Powder.	
Colour	: Various.	
Odour	: Characteristic.	
Odour threshold	: No data available.	
рН	: 12 - 13	
Relative evaporation rate (butylacetate=1)	: No data available.	
Melting point	: No data available.	
Freezing point	: No data available.	
Boiling point	: No data available.	
Flash point	: No data available.	
Self ignition temperature	: No data available.	
Decomposition temperature	: No data available.	
Flammability (solid, gas)	: Not flammable.	
Vapour pressure	: No data available.	
Relative vapour density at 20 °C	: No data available.	
Relative density	: No data available.	
Solubility	: No data available.	
Log Pow	: No data available.	
Log Kow	: No data available.	
Viscosity, kinematic	: No data available.	
Viscosity, dynamic	: No data available.	
Explosive properties	: No data available.	
01/15/2016	EN (English)	4/7

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

according to the Hazard Communication Standard (CFR2	9 1910.1200) HazCom 2012.
Oxidising properties	: No data available.
Explosive limits	: No data available.
9.2. Other information	
VOC content	: 0%, Not applicable; 0 wt, Not applicable.
VOC content	. 0%, Not applicable, 0 wi, Not applicable.
SECTION 10: Stability and reactivity	
10.1. Reactivity	
No dangerous reaction known under conditions	of normal use.
10.2. Chemical stability	
Stable under normal storage conditions. Keep di	v in storage
10.3. Possibility of hazardous reactions	
No dangerous reaction known under conditions	of normal use.
10.4. Conditions to avoid	
Incompatible materials. Moisture.	
10.5. Incompatible materials	
Wet cement is alkaline and incompatible with ac	d, ammonium salts and aluminum metal.
10.6. Hazardous decomposition products	
May include, and are not limited to: oxides of can	DON.
SECTION 11: Toxicological informat	ion
11.1. Information on toxicological effects	
Acute toxicity	: Harmful if swallowed.
Amerimix Fiber Base Coat Concentrate Stud	
LD50 oral rat	~1880 mg/kg, rat
LD50 dermal rabbit	No data available.
LC50 inhalation rat	No data available.
Ashes, residues (68131-74-8)	
LD50 oral rat	> 2000 mg/kg
Iron oxide (Fe2O3) (1309-37-1)	
LD50 oral rat	> 10000 mg/kg
Quartz (14808-60-7)	500 ma/kg
LD50 oral rat	500 mg/kg
Magnesium oxide (MgO) (1309-48-4)	
LD50 oral rat	>5000 mg/kg
Calcium hydroxide (1305-62-0)	
LD50 oral rat	7340 mg/kg
Magnesium hydroxide (1309-42-8)	
LD50 oral rat	8500 mg/kg
Calcium sulfate (7778-18-9)	
LD50 oral rat	> 3000 mg/kg
Limestone (1317-65-3)	
LD50 oral rat	6450 mg/kg
Calcium oxide (1305-78-8)	
LD50 oral rat	>2000 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes skin initiation. : Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity Carcinogenicity	: Based on available data, the classification criteria are not met.
Carenogenicity	: May cause cancer.

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Iron oxide (Fe2O3) (1309-37-1)	
IARC group	3 - Not classifiable
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Causes damage to lungs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
SECTION 12: Ecological informatior	
12.1. Toxicity	
Ecology - general	: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.
12.2. Persistence and degradability	
Amerimix Fiber Base Coat Concentrate Stu	CCO
Persistence and degradability	No data available.
12.3. Bioaccumulative potential	
Amerimix Fiber Base Coat Concentrate Stu	CCO
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
Amerimix Fiber Base Coat Concentrate Stu	
Ecology - soil	No data available.
••	
12.5. Other adverse effects	
Other adverse effects	: No data available.
SECTION 13: Disposal consideration	1S
13.1. Waste treatment methods	
Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.
SECTION 14: Transport information	
In accordance with DOT	
14.1. UN number	
Not applicable	
14.2. UN proper shipping name	
Not applicable	
14.3. Additional information	

: No supplementary information available.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 15: Regulatory information 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Gypsum (Ca(SO4).2H2O)	CAS No 13397-24-5

15.2. US State regulations

Amerimix Fiber Base Coat Concentrate Stucco	
State or local regulations	This product contains Crystalline Silica, Quartz and may also contain other chemicals known
	to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information	
Indication of changes	: None.
Date of issue	: 06/10/2014
Data sources	: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product